

Essential instruments

Engine & industrial emissions July 2022 Unpriced











Welcome to our latest Engine & Industrial Combustion Emissions Testing catalogue

We are the only UK manufacturer of engine & industrial exhaust gas analysers with a 10 year warranty if serviced annually. From Autos to Zambonis, buses to boilers & cars to container ships, we have a KANE analyser for you

All backed by KANE CARE - Our promise to never let you down and winner of the Queen's Award for Innovation

Here's what's new:

- ★ KANE EGA Our range of Exhaust Gas Analysers adaptable to your needs
- ★ KANE958 & 988 Commercial & Industrial Gas Analysers with flexible sensor combinations & **KANE** COD **LINK**[™] technology for wireless measurement of CO, temperature, airflow & humidity
- ★ KANE-GCU Portable Gas Conditioner for MCERTS & TUV compatible NO2 & SO2 emissions measurements for our KANE958 & 988
- ★ KANE-TCAM Thermal Imaging Camera Combines surface temperature & real-time thermal imaging See the unseeable!
- ★ KANE78 & KANECO2 Unique ID card holder with personal Carbon Monoxide (CO) alarm & portable indoor air Carbon Dioxide (CO2), temperature & humidity monitor

If you're not sure what you need, please call us on **0800 059 0800** or visit www.kane.co.uk



Working with leading gas industry companies including























































Contents

Engine Exhaust Gas Analysers	3-12
Which analyser & kit is right for me?	5-6
KANE-EGA1/2/3	7-8
KANE-EGA4/5	9-10
KANE-AUTO600 Smokemeter	11-12
Industrial Combustion Analysers	13-26
Which analyser & kit is right for me?	15-16
KANE958	17-18
KANE988	19-20
KANE LINKTM	21-24
KANE9206 Quintox	25-26
App & Personal Protection	27
Indoor Air Quality	28
Pressure Meters	29-30
Leak Detection	31
Thermal Imaging KANE-TCAM	32
Temperature & Probes	33
Electrical Test	34
Combustion & Exhaust Probes	35-37
Accessories / Consumables	38-40
UKAS Calibration	40
Welcome to KANE CARE	41-44
KANE Merchandise	45
KANE Online	46
Contact Us	47

Trade Associations & CO Safety Awareness



























Global Quality, Environment, Health & Safety



















Auxiliary Heaters to Zamboni Machines



Engine Exhaust Testing see pages 5-12

Which KANE EGA is right for me?




EGA with wireless module, EP1 probe, charger & carry bag





KANE Asset Manager (KAM) Manage your EGA recertification with FREE postage





What do I get?

KANE-EGA1, 2 & 3





Optional extra:

KANE-IRP3 Infra Red Printer





For full details see pages 6-10





KANE-EGA1/2/3



Spot check engine safety & efficiency

What do I get?



Handheld exhaust analyser for up to 3 gases Your EGA - Your way

What are the options?



Select up to 3 sensors from these options:

CO 0-10,000ppm*

CO 0-10% (100,000ppm)*

CO2 0-20%

O2 0-21%

NO 0-1500ppm

Which EGA would I like?



Single Gas

Two Gas

Three Gas



Wireless module & KANE LINKTM, EP1 emissions probe, USB1 charger & 17820 carry bag









KANE-EGA1

KANE-EGA2

KANE-EGA3

*One CO sensor option only

Exhaust Gas Analyser with 6 line display

- Spot check faulty exhausts & catalytic converters
- Test diesel engine NOx emissions
- Test vehicle & warehouse air quality
- Check vehicle cab heaters
- Compact & quick to use with large display

Applications

- Test performance & safety of any fossil fuelled car & commercial vehicle
- Also tests: fork lift trucks, ice rink machines, in vehicle heaters, motorbikes, scooters, generators & compressors

Measures (depending on sensor fitted)

- CO 0-10,000ppm
- CO 0-10%
- CO₂ 0-20%
- O₂ 0-21%
- NO 0-1500ppm

Calculates (if NO sensor fitted)

NOx 0-1500ppm

Fuel Types

- Petrol/Gasoline
- LPG
- CNG
- Diesel

Features

- Rotary dial & 6 line display for ease of use
- Wireless connects to KANE LIVE & 3rd party Apps
- Wirelessly connect to optional KANE LINKTM enabled devices
- Store up to 99 tests
- Compact design with protective rubber sleeve & magnets for hands free operation
- Rugged & portable with protective magnetic rubber sleeve for "hands-free" use
- Integrated water trap with replaceable particle filter
- USB Charger with rechargeable, long life batteries
- 10 year warranty when serviced & recertified by KANE
- Backed by KANE CARE We promise to never let you down or your money back



Diesel Generator NOx test





In cab heater CO₂ test with EP5 probe

Probe & accessory options

EP2	300mm exhaust probe with 6M tubing & in-line particle filter	
EP3	230mm motorcycle exhaust probe with 1.5M tubing	
EP4	As EP3 & measures exhaust temperature	
EP5	In cab heater probe	
KANE-IRP3	Infra Red Printer	

KANE LINK options

KANE-WPCP2	Wireless LINK temp clamp probes - connect as a pair	
KANE-DTHA2	Wireless LINK airflow, temp & RH	
KANE79	Wireless LINK CO monitor to 999ppm	

See KANE LINK devices on pages 21 - 24





KANE-EGA4/5

Diagnose engine performance with unique NDIR sensor technology

What do I get?



Handheld exhaust analyser for 4 or 5 gases Your EGA - Your way

What are the options?



KANE-EGA4	KANE-EGA5
CO 0-10%	CO 0-10%
CO2 0-20%	CO2 0-20%
HC 0-5,000ppm	HC 0-5,000ppm
O2 0-21%	O2 0-21%
Lambda 0.8-1.2	Lambda 0.8-1.2
	NO 0-1500ppm

Which EGA would I like?



Supplied with:

 Wireless module, EP1 emissions probe, CL5 USB Lead, CU12VDC2A21 charger & 14102/2 carry bag







Four Gas



KANE-EGA4

Five Gas



KANE-EGA5

Exhaust Gas Analyser with graphic display

- Unique Non-Dispersive Infrared (NDIR) analyser designed to meet official test standards
- Measure any engine exhaust
- Diagnose existing & potential engine / exhaust / catalytic converter faults quickly
- HC helps identify fuel flow, misfire & EVAP problems
- Ideal for pre-compliance & roadside compliance testing - local laws may apply
- Lambda & AFR helps improve engine efficiency & fuel consumption
- Test vehicles under real world driving conditions
- Take EGA to vehicle, not vehicle to analyser

Applications

- Real time vehicle / engine testing in workshop or on road
- Instant assessment of engine, exhaust system & catalytic converter
- Vehicle smog checks, tune ups & diagnostics
- Check repair work with before & after test
- Maintain engines to manufacturers specification

Measures

- CO 0-10%
- O₂ 0-21%
- CO₂ 0-20%
- NO 0-1500ppm optional
- HC 0-5000ppm

Calculates

- Lambda/AFR 0.8-1.2
- NOx 0-1500ppm optional

Fuel Types

- Petrol/Gasoline
- CNG
- LPG
- Diesel

Features

- Large graphic display
- Unique NDIR sensor package for accurate, fast measurements
- Wireless connects to KANE LIVE & 3rd party Apps
- Fast warm up
- Rechargeable battery with minimum 4 hour life, AC & 12v in-vehicle chargers as standard
- Language options English, French, German, Spanish, & Italian
- Rugged & portable with protective rubber sleeve
- Document test results with optional KANE-IRP3 printer
- 10 year warranty when serviced & recertified by KANE
- Backed by KANE CARE We promise to never let you down or your money back





Fork lift truck emissions test



Exhaust analysis & engine diagnostics

Sensor, probe & accessory options

NOX 4-2+	NOx upgrade 0-1500ppm for KANE-EGA4	
EP2	300mm exhaust probe with 6M tubing & in-line particle filter	
EP3	230mm motorcycle exhaust probe with 1.5M tubing	
EP4	As EP3 & measures exhaust temperature	
EP5	In cab heater probe	
KANE-IRP3	Infra Red Printer	

SMOKE PEAK 0.04k UNITS MODE 9/0

Supplied with:

 EPDEA1 high temp exhaust probe, SM12993 neutral filter, KANE-IRP3 portable infrared printer, CA13600-3 in vehicle 12V charger & 19603 AC Charger



KANE-AUTO600

Portable Diesel Smokemeter

- Unique battery & mains powered smokemeter designed to meet official test standards
- Extracts vehicle exhaust into a smoke sample chamber with a near monochromatic visible light source (NMVLS)
- NMVLS obscuration allows accurate measurement of vehicle smoke density
- Smoke density displayed in real time on wireless handset



Low Emissions Zone test







Applications

- Partial flow tester for Continuous & Peak diesel engine exhaust smoke testing
- Meets recognised accuracy & repeatability standards for Cat A (Cars & light commercial) & Cat B (Commercial) vehicles

Measures

Hartridge units (%H) & k (/m)

Fuel Types

Diesel

Features

- Remote handset with large display & easy operation
- Fully portable & self powered Rechargeable battery with minimum 3 hour life
- AC & 12v in-vehicle chargers as standard
- Compact, light design easy to position on all vehicle exhausts
- Handset connects via wireless or cable
- Peak measurement %Hu & /m
- Self calibration after each test maintains accuracy
- Document test results with KANE printer supplied as standard
- 10 year warranty when serviced & recertified by KANE
- Backed by KANE CARE We promise to never let you down or your money back





Wireless smoke test



Diesel engine smoke test





Pollution spot test





Boilers to Marine Engines





Efficiency & Emissions Testing

see pages 15-28

Which KANE958 & 988 kit is right for me?





& CHSP6 probe

Independently tested by TUV SUD to EN50379 Use for BS7967 & TB143





Manage your FGA recertification with FREE postage

CP2T



What do I need?

KANE958

KANE988

KANE9206

Flue Gas Analyser	~	V	V
Temp & Pressure	·	✓	✓
Wireless connectivity	V	✓	·
Sensor upgrades	Up to 4	Up to 9	Up to 9
KANE CO LINK	V	✓	N/A
Indoor air quality	KANE-DTHA2*	KANE-DTHA2*	N/A
MCERTS	Pending	Pending	Pending
NO ₂ & SO ₂ gas conditioning	KANE-GCU*	KANE-GCU*	KANE-GCU9206**
Large graphic display		✓	V
> 5 MW boiler / 50 mbar draught		✓	V
Continuous monitoring			KANE-GCU9206*
Active flow control			V
GPS location identity			✓
Integral printer	7		V
_			



What do I get?



Optional extra:

KANE-IRP3 Infra Red Printer



KIT



PRO KIT



OIL KIT

For full details see pages 17-28





KANE958

 Gas analyser with CO sensor over-range protection, CP2T combustion probe & USB1 charger, 2 psi pressure sensor & pressure hose







K CP2T



Independently tested by TUV SUD to EN50379 Use for BS7967 & TB143

KANE958



Kit options with analyser & probe





KANE958 KIT

KANE958 PRO KIT



KANE CO LINK

Our wireless measurement & future proof promise Use your KANE LINK analyser & optional devices to safely measure:

- Boiler & Heat Pump flow & return
- Home & workplace IAQ, airflow & humidity
- CO migration tests up to 4 simultaneously
- 100% H2 appliances when required
- HVO appliances when required

KANE LINK options:

INAINE EININ OPTIONS:		
KANE-WPCP2	Wireless LINK temp clamp probes - connect as a pair	
KANE-DTHA2	Wireless LINK airflow, temp & RH	
KANE79	Wireless LINK CO monitor to 999ppm - connect up to 4	

See KANE LINK devices on pages 21-24

Commercial analyser

KANE958 Gas Analyser measures O2 & CO with over-range protection

- Test any boiler up to 5 MW or 50 mbar stack draught
- Measures O₂ to 21% and CO to 10,000ppm with H₂ compensation
- Option to measure CO to 100,000ppm / 10% & 2 toxic gases
- Easy to use rotary dial with large display
- Purge pump protection prevents accidental damage to CO sensor
- Wireless as standard connect to optional KANE LINKTM enabled devices
- Hydrogen (H₂) ready up to 20% blend
- MCERTS (pending) compatible with optional KANE-GCU Gas Conditioning Unit for NO2 & SO₂

Applications

- Install & service domestic oil & gas appliances - optional emission sensors for local regulations
- Commission & service industrial boilers, marine boilers, engines & compressors
- Safety checks CO in rooms or around appliances
- Combustion performance checks
- Combustion efficiency checks
- Flue Draught

Measures

- O₂ 0-21% ppm
- CO 0-10,000ppm H2 compensated
- Differential temperature
- High accuracy differential pressure meter +/- 160mbar
- NO 0-5,000ppm (option)
- NO₂ 0-1,000ppm (option)
- High Range CO 0-10 % (option)
- SO₂ 0-5,000ppm (option)

Calculates

- CO₂
- Excess air
- NOx (option)
- CO/CO₂ ratio
- Combustion efficiency
- Reference gases

Fuel Types

- Natural Gas Butane
- LPG
- Light oil
- Heavy oil
- Coke
- Propane Coal
- Biogas Wood pellets

Features

- Rotary dial & 6 line display
- View, hold, store & print test results to optional KANE-IRP3 printer or KANE LIVE & 3rd party apps
- 10 year warranty when serviced & recertified by KANE
- Backed by KANE CARE We promise to never let you down or your money back



Flue Gas Analysis

Sensor options - up to 2

NO 0-5,000ppm	
NO2 0-1,000ppm**	
SO2 0-5,000ppm**	
CO 0-10% replaces standard CO sensor*	

*not with optional SO2 sensor

Probe & accessory options

CHSP5	285mm high temperature PTFE lined smoke probe with removeable shaft & 4m neoprene hose	
CHSLP5	1m high temperature PTFE lined smoke probe with removeable shaft & 4m neoprene hose	
KMCE10	10m hose & thermocouple extension	
KANE-GCU**	Gas conditioning unit	















KANE988

 Gas analyser supplied with CP2T combustion probe, CU12VDCA21 charger, 20106 backpack, MSC00017 handset pouch & 2 psi pressure sensor & pressure hose



Independently tested by TUV SUD to EN50379 Use for BS7967 & TB143



KANE988





Testing boiler efficiency





Boiler trend analysis



Testing boiler emissions



Optional extra:

KANE-GCU*

Gas conditioning unit

Full details see page 40

Industrial analyser

KANE988 Industrial 9 Gas Analyser

- As KANE958 plus:
- Test any size boiler with high suction pump
- Also measures CO to 100,000ppm / 10%, HC to 5000ppm & CO2 to 20%
- Option for 4 toxic sensors
- Large keypad & graphic colour display

Applications

- Install, commission & service large oil, gas or biomass appliances - optional emissions sensors for local regulations
- Accurate NO₂ & SO₂ measurements with optional KANE-GCU gas conditioning unit
- Safety checks
 - CO in a room or around an appliance
- Combustion performance checks
- Combustion efficiency checks
- Flue draught

Measures (Standard Kit)

- O2 0-21%
- CO 0-10,000ppm
 - H₂ compensated
- CO 0-10%
- CO2 0-21%
- HC 0-5,000ppm
- Temperature inlet / flue gas / differential / ambient
- High accuracy differential pressure meter +/- 160mbar

Calculates (Standard Kit)

- CO₂ 0-99%
- CO/CO₂ ratio
- Excess air
- Combustion efficiency
- NOx (if NO sensor fitted)

Fuel Types

- Natural Gas (x2)
- Wood Pellets
- - Kinsale Gas Gascor
- Heavy oil / 35 sec Propane

Town Gas

Bio Gas

- Anthracite
- LPG
- Butane
- Coke
- User fuel (x5) Light oil / 28 sec
- **LPG** Coal

Features

- Supplied with CP2T Teflon lined flue probe
- View, log & store up to 8,000 test results to transfer to KANE LIVE app, PC or optional KANE-IRP3 printer
- Long life battery recharged in situ
- 10 year warranty when serviced & recertified by KANE
- Backed by KANE CARE We promise to never let you down or your money back



Our wireless measurement & future proof promise



Gas Engine Testing with optional CHSP5 probe

Sensor options - up to 4

NO 0-5,000ppm	
NO2 0-1,000ppm*	
SO2 0-5,000ppm*	
H2S 0-200ppm	

Probe & accessory options

CHSP5	285mm high temperature PTFE lined smoke probe with removeable shaft & 4m neoprene hose	
CHSLP5	1m high temperature PTFE lined smoke probe with removeable shaft & 4m neoprene hose	
KMCE10	10m hose & thermocouple extension	
KANE-GCU*	Gas conditioning unit	






















Wireless measurement & future proof

KANE-WPCP2



Wireless Pipe Clamp Temperature Probes x2

Features:

- Wirelessly measure & display system temps including:
 - Flow & return
 - Boiler commissioning test
 - Monobloc Heat Pumps
- See real time results on your KANE FGA
- Works in tight spaces for pipe diameters up to 38mm
- Instant On technology
- Range: 0 80°C
- Wirelessly connect to KANE LINKTM enabled devices
- 100m line of sight range





KANE-DTHA2



Features

- Wirelessly measure airflow, temperature & humidity
- See real time results on your KANE FGA
- Test A/C units & kitchen extraction fans
- Calculate outlet volume flow with dimensions & geometry
- Instant On technology
- Airflow: 1.1 to 20 m/s;

Temp: -20 to +50 C; RH: 0.1 to 99%

- Optional extender probe p/n: 20128
- IOS / Android App available
- Wirelessly connect to KANE LINKTM enabled devices



KANE79



Wireless Ambient Carbon Monoxide (CO) Monitor

Features

- Safely add Room CO tests to display & test reports when outside a potentially dangerous room
- Detects 0 999ppm CO to 1 ppm resolution
- Green, Yellow, Red alarm & audible alert with Max & Hold
- Wirelessly connect to KANE LINKTM enabled devices
- Test up to 4 rooms simultaneously



Alarm LED Indicator Levels

0 to 1 ppm

2 to 9 ppm

10 to 19 ppm

≥20 ppm

KANE79 is for ambient testing only

DO NOT place in flue gas or warm air streams



KANE CO LINK

Use our **KANE** COD LINK™ devices & your KANE LINK™ enabled FGA / EGA to balance heating systems, check A/C units, kitchen fans or test rooms, boiler houses, & truck cabs for CO Compatible with KANE458s, 958, 988 & KANE-EGA1/2/3 analysers



KANE79



Wireless Ambient & Personal CO Monitor Features

- CO 0 999ppm to 1ppm resolution
- Large display with visual & audible alarms, MAX & Hold display options
- Safely test rooms & passenger compartments from outside using your KANE LINKTM analyser
- View, store & transfer CO tests on your KANE LINKTM analyser or KANE LIVE app
- Perform 4 tests simultaneously linking up to 4 KANE79 to your KANE LINKTM analyser
- Quickest way to perform UK CMDDA1 multiple room CO migration tests

Alarm LED Indicator Levels

0 to 1 ppm

2 to 9 ppm

10 to 34 ppm

≥35 ppm

KANE79 is designed for ambient testing only. DO NOT place the instrument in flue gas or warm air streams

CPS₁

Optional Extra: Combustion probe stand 2.1m max height



Wireless measurement on a KANE FGA / EGA

CO monitoring & investigation











KANE9206

Supplied with remote handset, pressure connectors, PTFE lined CHSP6 probe, CL5 USB Lead, 19603 charger & heavy duty case



KANE9206



Industrial Boiler & Burner Commissioning







Industrial analyser

KANE9206 Quintox - Industrial & semi continuous 9 Gas Emissions Monitor

- Test boilers with stack draught over 50 mbar with high suction pump
- Long term unattended testing with 64,000 test memory, remote handset & large graphic display
- Unique 5 gas sensor technology O₂ 0-21%, CO 0-10,000ppm H₂ compensated CO 0-10%, HC 0-5000ppm & CO2 0-20%
- Option for 4 toxic sensors
- Perform unattended boiler commissioning tests with automatic fresh air purge and optional WTS9206P automatic water trap
- Perform MCERTS (pending) compatible emissions tests with optional gas conditioning unit, heated line & probe
- Perform cold condition tests with optional KHSA sensor heater

Measures (Standard Kit)

- O₂ 0-25%
- CO 0-10,000ppm H₂ Compensated & 10% NDIR
- CO₂ 0-21%
- HC 0-5,000ppm
- Flue Temp 0-1100°C
- Pressure 0-150 mbar

Calculates (Standard Kit)

- CO₂ 0-99%
- Excess Air
- NOx (if NO sensor fitted) Combustion efficiency
- Pitot tube measurement (if using 3rd party pitot tube)

Fuel Types

- Natural Gas (x2)
- Wood Pellets
- Kinsale Gas
- Heavy oil / 35 sec Propane

- Town Gas Bio Gas
 - LPG
- Gascor
- Butane
- Coke

Anthracite

- User fuel (x5) Light oil / 28 sec
- Coal

Features

- Large Graphic Display with 15 lines of text & data
- Optional Gas Conditioning Unit for accurate NO2 & SO₂ measurement
- Wireless & cable link between Analyser & Handset for remote monitoring
- GPS to pinpoint exact test location
- Wireless & USB link to PC
 - Use KANE LIVE software for "real time" monitoring or test results transfer to a PC, tablet or smartphone
- Large internal memory to store up to 64,000 tests
- Main Purge
 - Zero & refresh sensors without removing probe from flue
 - Automatic sensor 'over range' protection
- Active Flow Control
 - Pump speed auto adjusts to stack pressure changes & filter dirt
- Integral printer & option to use KANE-IRP3



Marine Engine Emissions Testing

Sensor options - up to 4

KH2S/Q	H₂S 0-1000ppm sensor*	
KNO1H/Q	NO 0-5000ppm sensor	
KNO2/Q	NO₂ 0-1000ppm sensor*	
KSO2H/Q	SO₂ 0-5000ppm sensor*	

Probe & accessory options

CHSLP6	1m high temperature PTFE lined smoke probe with removeable shaft & 4m neoprene hose			
KMCE10	10m hose & thermocouple extension			
KHSA	Toxic Sensors Heater			
WTS9206P	Automatic emptying water trap - not needed with KANE-GCU9206			
KANE-GCU9206*	Gas Conditioning Unit & Automatic Water Trap			
KMHL3000*	3m Heated Line to 120°C			
KMHP1200*	1m Heated Probe to 120°C			

- Backed by KANE CARE We promise to never let you down or your money back
- 10 year warranty when serviced & recertified by KANE



Compatible with Apple & Android Devices







KANE LIVE FREE FROM THE APP & PLAY STORE

0.0%

1.45

28ррп

51,5°C

22.870

KANE LIVE connects & controls your KANE Flue Gas Analyser



- View, share & record live tests
- Snap shot test results like a printer
- Generate PDF reports & certificates*
- Add company & user profiles
- Send test results in CSV for spreadsheets
- GPS tag your location
- Control analyser pump, torch & fresh air purge
- Help via in-app guides & KANE Knowledge Centre
- Quick link to kane.co.uk, e-mail & social media for FAQs & feedback

IMPORTANT! KANE analysers must have a wireless module fitted. Contact us for more details



Personal Protection

KANE78

iD Safe™ Personal CO Alarm & ID Holder


Features

- 2 in 1 CO alarm & ID badge holder
- Protects you from high CO levels wherever you are
- Displays your ID badge
- Audible & visual alarm over 20ppm CO
- 2 years "fit & forget" life
- Supplied with lanyard



Alarm Levels

In accordance with EH40/2005 (Fourth Edition 2020)



KANE78 is a personal CO alarm - Once activated, it operates for up to 2 years if alarm doesn't activate



Audible alarm ≥ 75db

^{*} market dependent

Test up to 4 rooms simultaneously



KANE79



Wireless Ambient & Personal CO Monitor

Features

- CO 0 999ppm to 1ppm resolution
- Large display with visual & audible alarms, MAX & Hold display options
- Safely test rooms & passenger compartments from outside using your KANE LINKTM analyser
- View, store & transfer CO tests on your KANE LINKTM analyser or KANE LIVE app
- Perform 4 tests simultaneously linking up to 4 KANE79 to your KANE LINKTM analyser
- Quickest way to perform UK CMDDA1 multiple room CO migration tests



Indoor Air Quality



KANE-CO2

Indoor Air Quality (IAQ) Carbon Dioxide Monitor

Application

Monitors CO₂ concentration, relative humidity & temperature


Measures

- Ambient CO₂ 0-5000ppm
- Relative humidity RH 5-95%
- Temperature 0°C to 90°C / 32°F to 195°F

Features

- Large display & touch button operation
- Low drift CO₂ NDIR sensor with long lifespan
- Audible & visible alarm
- Chart with variable time zoom levels
- CO₂ / RH / Temperature monitor tracer
- Auto-calibration on power on & manual calibration
- Max / min value display in real time
- Supplied with USB cable & manual

LED Indicators





Health & Safety Executive (HSE) report CO2 monitors help identify poor ventilation increasing risk of COVID Aerosol transmission

Pressure Meters



Contents: Pressure meter supplied with HARHOSE pressure hose, rubber sleeve & hard carry case MSC00238

KANE3500

High Accuracy Differential Pressure Meters with temperature compensation & test results data transfer

Description

- Measure flue draft & gas / air ratio valves on high efficiency boilers
- Test Smart Meter integrity after installation
- Automatic Tightness Testing on KANE3500-1 & KANE3500-2
- · Print test results with user details to optional printer
- Wireless data transfer option

Features

- 5 versions available see table for specifications
- KANE3500-1 Resolution to 0.1 pascal / 0.001 mbar
- Temperature compensated for superior accuracy
- Switchable between high & low resolution
- Switchable between: mbar, Pa, hPa, kPa, mmHg, mmH2O, inH2O & PSI
- Data hold & max / min recording
- 10 year warranty when serviced & recertified by KANE
- Backed by KANE CARE We promise to never let you down or your money back



KANE3500			
	KANE3500-1	Range ± 1 psi / 80 mbar	
	KANE3500-2	Range ± 2 psi / 160 mbar	
	KANE3500-5	Range ± 5 psi / 400 mbar	
	KANE3500-15	Range ± 15 psi / 1040 mbar	
	KANE3500-30	Range ± 30 psi / 2070 mbar	
	WLEM-Q	Wireless iOS / Android module added to any KANE3500	





KANE Asset Manager (KAM)

- Fastest way to manage recertification with FREE postage

KANE3200

High Accuracy Differential Pressure Meter

Description

 Easy to use, two button pressure meter with integral magnet for hands free operation

Features

- Switchable between: mbar, Pa, hPa, kPa, mmHg, mmH2O, inH2O & PSI
- One button zeroing
- Long battery life

 10 year warranty when serviced & recertified by KANE

Backed by KANE CARE -We promise to never let you down or your money back

Contents: Pressure meter supplied with HARHOSE pressure hose, rubber sleeve & HARPOUCH soft pouch





PRD2

Pressure Relief Device



Description

 When completing a tightness test the PRD2 lets you bleed off any excess gas pressure

KANE-IRP3

LOG
TIME 15:55 12/05/21

Let-by Test

PRS_1 Mbar 10.15
PRS_2 Mbar 10.10
Let-by Mins 1.00

Tightness Test

PRS_3 Mbar 20.17
PRS_4 Mbar 20.12
APR3 Mbar 9.05
STABIL'N Mins 1:00
TIGHTN'S Mins 2:00

Customer

Appliance

Infra-red printer

• Supplied with USB1 charger

Produce print outs using optional printer KANE-IRP3 Infra-Red Printer



Leak Detection

KANE-EGD

Combustible Gas Leak Detector

 EGD detects combustible gas leaks from:
 20ppm Hydrogen
 50ppm Methane & Propane

Gases Detected

Acetone Gasoline/Petrol
Alcohol Hydrogen
Ammonia Industrial Solvents
Benzene Jet Fuel
Butane Lacquer
Ethylene Methane

Features

- Flexible goose neck probe
- Solid state semi conductor sensor
- Detection levels <50ppm methane
- Indicators audible tic rate & visual multi-coloured LEDs
- Tip light

Supplied with carry case PN: MSC00239











Visual 3 colour LED indication

KANE-RGD

Refrigerant Gas Leak Detector

 RGD detects refrigerant gas leaks of: CFC, HFC, HCFC, R11, R22, R134a etc

Features

- Flexible goose neck probe
- Solid state semi conductor sensor
- Detection levels 10g / year based on R134a
- Indicators audible tic rate & visual multi-coloured LEDs
- Tip light

Supplied with carry case PN: MSC00239



KANE-GLD

Combustible Gas Leak Detector

Applications

• Pin-point small combustible gas leaks

Gases Detected - same as KANE-EGD


Features

- Flexible shaft 180mm long
- Solid state semi conductor sensor
- Audible & visual indicators
- >50ppm methane detection limit



Leak detectors do not measure gas levels

GLD





Thermal Imaging Camera


Combines surface temperature measurement & real-time thermal imaging - See the unseeable!

Features:


- Large colour display & on-screen cursor
 - Accurately locate temperature hotspots
- 3GB SD Card Data storage
 - Store up to 20,000 images that can be extracted through USB
- Rechargeable battery
 - 3 hours during normal operation
- Temperature -20 +300°C
- Four types of surface measurement modes:
 - Coarse surface
- Semi-matte surface
- Semi-shiny surface
- Shiny surface
- Ideal problem solver for:
 - Plumbing & Heating
 - Radiators, underfloor heating, energy auditing or water damage
 - Automotive
 - Heated seats & windows, high resistance in wiring, overheating wiring or components
- Supplied with USB charger & hard carry case MSC00237

Display Screen 2.8 inch full view TFT display






e=0.95



Underfloor heating

MAX:39.2°C MIN:14.8°C 10:47



Blocked radiators

Invisible leaks

Temperature

DT200

Digital Thermometer

Description

- Durable, versatile & fast responding
- Uses J, K or T thermocouple types
- High accuracy
- Backlight display is easy to read

Features

- Temperature -200 to +1370°C / -328 to +2498°F
- Time stamped multifunction record
- Relative function displays temperature change
- Data hold
- Protective rubber boot
- Dual input, triple display, differential temperature (ΔT)





H & V KIT

Heating & Ventilating Kit includes DT200

Features

- See DT200 for features & specification
- Supplied with:
 DT200 Differential Thermometer
 2 x KWA1 wrap around pipe probes
 1x KAL1 air liquid probe
 1 x KSP1 surface probe
 - 1 x KFT1 flexible probe
 - Carry case

KANE-INF165C

Infra-Red Thermometer





Description

Easy, comfortable non-contact temperature testing

Measures

• Temperature -60 to +550°C / -76 to +1022°F

Features

- Circular laser targeting
- Distance to spot ratio 12:1
- Fixed emissivity 0.95
- Max value capture
- Auto off

Temperature Probes

KPCP2



Pipe clamp probe Measures -40 to +150°C Jaw dia. up to 50mm

KAL1



KSP1

Light duty surface probe -50 to +500°C



KSP2

Heavy duty surface probe -50 to +500°C



KWA1

Wrap around pipe probe Measures -40 to +150°C

Electrical Test

For full specifications visit www.kane.co.uk



See TB118 & 'Electricity at works regulations 1989' for more information







KANE-VCT KIT Contents:

- KANE-VCT Voltage Tester
- KANE-PU690V Proving Unit
- Kit Carry Pouch
- Batteries

KANE-VCT KIT

Voltage & Continuity Tester with 690 volt **AC Proving Unit**

KANE-VCT KIT combines 2 great products & pouch:

KANE-VCT & KANE-PU690V

(also available separately)

KANE-VCT

Voltage & Continuity Tester

Features

- KANE Voltage & Continuity Tester with LED & digital voltage indication 12 - 690V AC/DC
- Includes Single Pole Detection & meets BS 61243-3:2014 GS38



KANE-DL469

AC 400A TRMS Clamp Meter

Features

- True RMS
- 400A AC
- 750V AC / 600V DC
- Resistance $40M\Omega$
- DC Microamps 2000µA
- Diode test
- Non-contact voltage detection

KANE-NCV3



KANE-PU690V

690v AC Proving Unit

Features

- Compact voltage proving unit
- Safely check voltage testers before using on live circuits

Features

- 24 to 1000V AC detection
- High / Low voltage detection
- Visual LED alert
- Audible alert

- Worklight
- Magnetic mount
- Auto power off
- Low battery warning



Combustion Probes



Combustion probes for standard temperature flue gases 600° C / 1112° F

I	1
ASP3 KIT	 Appliance sampling probe kit - grills, gas fires & general purpose 5mm diameter 2.2m flexible tube Separate handle & hose assembly
CP2	240mm probe6mm diameter2m neoprene hose
CP2S	100mm probe6mm diameter1.5m neoprene hose
CP2T	 240mm PTFE lined probe 6mm diameter 2m neoprene hose For KANE958, 975 & 988
CP30	 240mm combined flue gas & pressure probe 6mm diameter 2m neoprene hose
CP35	 300mm flexible probe 8mm diameter 1m neoprene hose
CP71	240mm probe6mm diameter0.9m neoprene hose
17320	6mm diameter depth stop cone
4290/2	8mm diameter depth stop cone
SM50472	10mm diameter depth stop cone for CP35
CPS1	Combustion probe stand 2.1m max height

CHSP5	 285mm high temperature smoke probe with removable shaft 8mm diameter 4m neoprene hose For KANE958, 975 & 988 	
CHSLP5	 1m high temperature smoke probe with removable shaft 8mm diameter 4m neoprene hose For KANE958, 975 & 988 	
CHSP6	 285mm high temperature smoke probe with removable shaft 8mm diameter 4m neoprene hose For KANE9206 	
CHSLP6	 1m high temperature smoke probe with removable shaft 8mm diameter 4m neoprene hose For KANE9206 	
KMCH	 285mm replaceable shaft with max temp 1250°C/2282°F 8mm diameter 	
KMCHL	 1m replaceable shaft with max temp 1250°C/2282°F 8mm diameter 	
KMHP1200	 1m Heated Probe 8mm diameter Use with KMHL3000 & KANE-GCU9206 For Quintox 9206 	

KANE-GCU

KANE-GCU Gas conditioning unit

Features

- Gas conditioning unit for KANE958 & 988
- Enables accurate NO2, SO2 & H2S measurements compatible with MCERTS (approval pending)
- Peltier chiller stops water condensate absorbing gas sample
- Supplied with KMCH 285mm High Temp 8mm dia probe, KMCE 10M hose & thermocouple extension & GCU1 power supply with 3M lead & EU, UK & USA adaptors

MSC00235

Hose & thermocouple extension lead for

KANE-GCU





Engine Exhaust Probes



We supply a range of exhaust probes for all applications

Standard Temp = 600° C/1112°F

EP1	 High temp stainless steel probe 4m neoprene tubing Insertion depth 350mm
EP2	 As EP1 plus: 6m neoprene tubing Insertion depth 300mm Includes in-line 70 µ filter (17702) Ideal for 'on road' & dyno testing
EP3	 High temp stainless steel probe for motorcycle exhaust testing 1.5m tubing Insertion depth 230mm
EP4	As EP3 plus: Thermocouple to measure exhaust temp
EP5	 In cab heater probe 4m neoprene tubing Insertion depth 350mm
EPDEA1	Diesel Smokemeter Exhaust Probe 1m For KANE-AUTO600







Accessories/Consumables 19278			
	KANE-IRP3 KANE Infra-Red Printer		charger for KANE101, 250, 251, 255, 425, 450, 451plus, 452NO, 455, 456, 457 & 458
	KANE-MSP KANE Smoke Test Kit	Panasonic Panasonic	B15 4x 2000 mAh rechargeable batteries. Note: battery make may differ
	18121 Oil gauge kit		CU12VDC2A21 Battery charger-100- 240V for KANE100,
and States	SP9 Smoke papers	* * * *	900 series, KANE975 & 988
1100000	& chart (for use with smoke probe options)		19603 15v DC charger / adapter for
	PRD2 Pressure Relief Device		PSL/UK
Spare Parts			UK power supply lead for KANE9206
	FB1 Blank filter for KANE9106 & KANE9206		PSL/UK/110 110 volt UK power supply lead for KANE9206
	SM11105 RD99 tip assembly	900	PSU00211 Power supply for
	17143 CD100A/LS1 sensor	Sensors	KANE-GCU
Batteries Chargers & P	ower Leads	_ 11	OS11 2 yr O2 sensor for
	USB1 USB charger for KANE258, 358, 458s, 958, KANE-EGA1,2, & 3		KANE9100, /01, /04, /06 & 9206
	18342 12V charger for KANE101, 250, 251, 255, 425, 450, 451 plus, 452NO, 455, 456,457 & 458		

Accessories/Consumables continued

Carry Cases				WSF2/5 (pack of
	17820		00	five) Water stop filters for KANE975 & 988
	Small carry bag			PF2/5 (pack of five) Filters for AF2. Also suitable for KM700, 701P,
	14102/2 Large carry bag		-	800, 900, 975, 988 KANE-EGA4 & 5
				PF400/5 (pack of five) Filters for KANECO91, 100,
	SM12516 Hard carry case for KANE-EGA4 & 5			101, 250, 251, 255, 258, 358, 425, 450, 451plus, 452NO, 455, 456, 457, 458, 458s, 504, 958, EGA1, 2 & 3
K	20106 Backpack			SF1/5 (pack of five) SF1 sulphur filters for KM9100,
	MSC00237 Hard carry case for KANE-TCAM			9101 (all models), KM9103, KM9106 & 9206
N AND N AND N AND	MSC00238 Hard carry case for KANE3500		\$100 m 1000	WN8 Filters for plastic bodied water traps (not in-line watertraps)
	MSC00239 Hard carry case for KANE-EGD & RGD		Paper & Ribbons	Такогиарој
Filters		<u> </u>		TP5 (pack of five) Thermal printer rolls
	AF2 Complete particle filter for KM9100, 9101, 9103, 9106 & 9206			for Infra-Red Printer KANE-IRP, KANE- IRP2 & KANE-IRP3
	AF9/5 (pack of five) Particle filters for KM9104 & KMCP40 flue probe			DP5 (pack of five) Printer ribbons for KANE9104, 9106 & 9206
HAPP	WSF1/5 (pack of five) Water Stop Filter for KANE458s & KANE958			

SM11103 | Replacement probe connector for KANE100, 101, 250, 251, 255, 451 plus, 452 NO, 455, 456, 457 & 458 | SM14980 | Replacement probe connector for KANE258, 358, 458s, 958, 975/988, EGA1, 2 & 3



451plus, 452NO, 455, 456, 457 & 458





UKAS Calibration

Why choose UKAS calibration certificates?

All KANE analysers & manometers receive calibration certificates traceable to National Standards.

KANE can supply optional ISO 17025 certificates for portable analysers measuring O2, CO, CO2 & NO.

ISO 17025 certificates have worldwide recognition with the highest standard of proof suitable for legal submission.

KANE is the only UK analyser supplier with a calibration laboratory accredited to ISO 17025 by UKAS.

UKAS is the only authority accrediting UK calibration laboratories - visit www.ukas.com/about/the-benefits

Call **0800 059 0800** for more information.










Welcome to KANE CARE

KANE CARE is our promise to never let you down or your money back

KANE CARE applies to any KANE FGA Service & Recertification booked online via www.kane.co.uk & www.kanetest.ie - some exclusions apply

For KANE CARE International Service & Recertification email: sales@kane.co.uk



- ★ Please register your analyser on our website to download the instruction manual from your KAM dashboard
- **★ PLEASE READ ALL SAFETY WARNINGS IN THE MANUAL**
- ★ Use our website to manage your Analyser, buy spares & other KANE products
- ★ Find FAQs on our website or on our YouTube Channel
- ★ Got a question? Call our Customer Service Team 7am 5pm any normal weekday

more info at: www.kane.co.uk/service-and-re-certification

THE QUEEN'S AWARDS
FOR ENTERPRISE
NNOVATION

www.kane.co.uk www.kane.eu

www.kanetest.ie

www.kane-care.com









UK & Ireland Same Day Despatch KANE CARE Service & Recertification



Register your analyser on www.kane.co.uk or www.kanetest.ie





Book & pay to Service & Recertify via your dashboard

Select FREEPOST for tracked carriage - UK & Ireland mainland only





Your analyser will be despatched the same day we receive it...

OR YOUR MONEY BACK*









International All Inclusive Price KANE CARE Service & Recertification



email sales@kane.co.uk with analyser name & serial number

Pay our all inclusive KANE CARE quote





Send your analyser & accessories

We will return free of charge* after KANE CARE Service & Recertification with 1 year warranty if under 10 years old











KANE CARE UK & Ireland Service & Recertification

KANE CARE is our promise to never let you down or your money back

- ★ 10 Year warranty with annual Service & Recertification
- ★ Same Day Service & Recertification guaranteed
- ★ 20 Year all inclusive pricing the price you see is the price you pay
- ★ Free next day tracked delivery to KANE & 9am next day return & Saturday
- ★ Theft protection 50% off when replacing your stolen KANE analyser

KANE CARE applies to any KANE FGA Service & Recertification booked online via www.kane.co.uk & www.kanetest.ie - some exclusions apply more info at: www.kane.co.uk/service-and-re-certification

KANE CARE International Service & Recertification

KANE CARE is our promise to never let you down or your money back

- ★ 10 Year warranty with annual Service & Recertification
- ★ 20 Year all inclusive pricing
- ★ Includes accessory repair or replacement as required including probe, charger, carry bag & printer
- ★ Free tracked return
- ★ Full test certificate & repair report


KANE CARE International applies to any KANE Analyser Service & Recertification booked & quote confirmed via sales@kane.co.uk - some exclusions apply more info at: www.kane.co.uk/service-and-re-certification

KANE Merchandise

Exclusive quality KANE brand merchandise available from our online shop

www.kane.co.uk/shop-products





















KCC108

KCC109

KCC111

KCC112 KCC114 (M or LG)

KANE MERCHANDISE

KCC103	KANE T-Shirt - Black
KCC104	KANE Polo Shirt Short Sleeve - Black
KCC105	KANE Sweat Shirt - Black
KCC106	KANE Zipped Hoodie - Black
KCC107	KANE Soft Shell Jacket - Black
KCC108	KANE Body Warmer - Black
KCC109	KANE Beanie Hat - Black
KCC110	KANE Mug & 5 Tea Bags
KCC111	KANE Multi Use Face cover
KCC112	KANE Face Mask (Non PPE)
KCC114M	KANE Socks 5-8
KCC114LG	KANE Socks 9-11



KANE Online



Join #teamkane & get social by following @KaneAnalysers on one of our online networks

We're proud of our online community - It's a great place to get feedback, keep you up to date, host competitions, share industry news & update you on life at KANE.

It's also easy to find our 'How to' videos so please join & see what you're missing.

Facebook Groups



'How to' Videos



#teamkane

















WE'VE GOT YOUR BACK

For more information contact

Customer Service 0800 059 0800

Email: sales@kane.co.uk

Outside UK Call +44 1707 375550

Distributed by:

www.kane.co.uk





We reserve the right to change prices, products & specifications without prior notice. Kit contents may change - Please check before purchase. Product images not to scale unless stated & colours may vary from those illustrated.

> KANE and the KANE logo (registered in the UK and elsewhere) are trademarks of Kane Group Limited, used under licence. All other marks are trademarks of their respective holders. © 2022 Kane International Limited